

Perifina Wall Reveal

3 in. & 4 in.

Recessed Mud-In Wall Cove Luminaire

Specification Submittal

Available in two sizes, Perifina Wall Reveal provides the ability to create a niche effect in a wall to provide not only an accent light but also an enhanced textured element to the wall. It is compatible with 5/8 in. drywall, easy to install, and unlike most solutions on the market, Perifina Wall Reveal can easily go around corners without light gaps or the need for complicated soldering.



Features & Benefits

- Designed to easily wrap around corners with no light gaps and no soldering
- Paintable backing plate ensures it blends in with any decor or color pallet
- Superior color rendering
- High R9 and R13 values
- 2-step MacAdam ellipse for unparalleled quality and consistency
- Complete UL listed luminaire

System Builder

Prefix	Fixture Type	Location	Output	CCT	Lens	Finish	Length (Minimum 2 ft.)	Lead	Lead Length
OP-REC-	WR3 3 in. aperture	I	White Light L2 200+ lm/ft (2.0W) L4 400+ lm/ft (4.0W) L6 600+ lm/ft (6.2W)	White Light 2200K 2400K 2700K 3000K 3500K 4000K 5000K	FRT	ALU	XXX Length in 1 in. increments - The fixtures come in segments up to 96 in. - If over 96 in., multiple segments of the profile will be supplied. The light engine will be cut to length with standard 3 ft. leads	1LEAD	XXX 1-120 in.
	WR4 4 in. aperture		RGBW+ RGBW6 600+ lm/ft (10.0W) RGBW8 800+ lm/ft (15.4W) RGBW10 1000+ lm/ft (20.4W)	RGBW+ 3000K					
			Tunable L4 400+ lm/ft (6.8W) L10 1000+ lm/ft (12.0W)	Tunable 30-18K					

Fixtures are supplied with Optique's remote Universal power supply supporting 0-10, 1-10V, MLV, ELV dimming and voltage input from 100V-277V.

Project Name: _____

Project Location: _____


Fixture Type: _____

SKUs: _____



Dimensions

Fixture Cross Section



Perifina Wall Reveal

3 in. & 4 in.

Recessed Mud-In Wall Cove Luminaire

Specification Submittal

Output

Indoor

White Light

L-Level		L2	L4	L6
Lumens (per ft.)	2200K	187	395	568
	2400K	191	399	619
	2700K	210	477	738
	3000K	219	458	715
	3500K	233	478	748
	4000K	239	496	755
	5000K	239	503	756
Wattage (per ft.)		2.0	4.0	6.2
Max Run Length* (ft.)		68	42	30

RGBW+

Output (lm/ft)		RGBW6	RGBW8	RGBW10
Lumens (per ft)	3000K	544	788	1015
Wattage (per ft.)		10.0	15.4	20.4
Max Run Length* (ft.)		19	12	9

Tunable

Output (lm/ft)		L4	L10
Lumens (per ft.)	30-18K	648	1124
Wattage (per ft.)		6.8	12.0
Max Run Length* (ft.)		20	12

*Maximum individual fixture per power feed.